

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 September 2005 (09.09.2005)


PCT

(10) International Publication Number  
**WO 2005/082663 A1**

- (51) International Patent Classification<sup>7</sup>: **B60K 6/04**, (74) Common Representative: **WAVECREST LABORATORIES LLC**; Intellectual Property Group, 45600 Terminal Drive, Dulles, VA 20166 (US).  
B60L 11/12, F02N 11/08
- (21) International Application Number: PCT/US2005/002018 (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 21 January 2005 (21.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
10/779,600 18 February 2004 (18.02.2004) US
- (71) Applicant (*for all designated States except US*): **WAVECREST LABORATORIES LLC** [US/US]; 45600 Terminal Drive, Dulles, VA 20166 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **CHO, Chahee, Peter** [US/US]; 2519 Long Meadow Road, Lansdale, PA 19446 (US). **KIM, Eun Shik** [KR/US]; 5360 Sequoia Farm Drive, Centreville, VA 20120 (US).
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PORTABLE RANGE EXTENDER WITH AUTONOMOUS CONTROL OF STARTING AND STOPPING OPERATIONS



(57) Abstract: A portable range extender can be used to supply electrical power to an electric vehicle operable by an electric traction motor. The portable range extender includes an engine, a dynamoelectric machine coupled to the engine by a shaft, an autonomous range extender controller for controlling operations of the range extender independently of a controller for the vehicle, and circuitry associated with the engine and machine. To start operation, electrical energization is applied from the vehicle battery to the dynamoelectric machine for operation as a motor to drive the shaft. As the shaft accelerates, the rotational speed of the shaft and the temperature of the engine are sensed. When the speed and temperature obtain predetermined thresholds, fuel is supplied to the engine and ignition is activated. The engine then operates as a prime mover to drive the shaft in lieu of the machine. After a period of engine prime mover operation, the machine is activated for operation as a generator to provide an electrical current output for charging the battery or supplying energy to the traction

motor. When range extender operation is to be stopped, fuel supply is cut off before ignition termination to avoid engine backfire.

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

~~PORTABLE RANGE EXTENDER WITH AUTONOMOUS CONTROL OF~~  
STARTING AND STOPPING OPERATIONS

Field of the Invention

The present invention relates to electric power supply devices, and more particularly, to  
5 portable stand-alone electric power supply devices that can be utilized as range extenders for electric vehicles.

Background Art

A typical range extender is provided as an integral part of a hybrid electric vehicle to  
10 improve its travel range. For example, U.S. patent No. 5,264,764 discloses a hybrid electric vehicle comprising an inverter/motor electric drive system, a vehicle controller, a range extender and a traction battery. The inverter/motor electric drive system is composed of an electric motor and an inverter/motor control unit. In response to a hand or foot actuated speed control actuator, a vehicle controller applies a torque command signal to the electric motor to drive the vehicle wheels through  
15 a transmission. The range extender, which includes an internal combustion engine and an alternator, is actuated by the vehicle controller to provide electric power to the inverter/motor drive system and/or the traction battery. The internal combustion engine rotationally drives the alternator to output electric power, which is applied to recharge the traction battery or to energize the motor. The inverter/motor control unit is responsive to the torque command signal to provide sufficient  
20 electric power from the traction battery and/or the range extender to the electric motor to drive the vehicle at a desired speed.

Another example of a range extender incorporated in a hybrid electric vehicle is disclosed in U.S. patents Nos. 6,622,804 and 6,333,620, which describe a series type hybrid electric vehicle including electric motors powered by a battery array, a vehicle control unit, an internal combustion  
25 engine and a generator driven by the internal combustion engine for charging the battery array. The internal combustion engine is controlled by the vehicle control unit to run continuously during operation of the vehicle. The charging of the battery array by the generator is controlled by the vehicle control unit depending on a driving mode of the vehicle, e.g., in accordance with power output, power consumption and rpm of the electric motors. The power generated by the generator is  
30 generally maintained constant but may be decreased if the state-of-charge of the battery array approaches an upper control limit at which the battery array may be overcharged, and may be increased if the state-of-charge approaches a lower control limit at which the battery array would be unable to drive the electric motors with enough torque to propel the vehicle appropriately.

The above-described systems are typical of a range extender that is designed specifically for  
35 the hybrid electric vehicle in which the range extender is installed. The range extender is controlled

by the vehicle controller to interact with the electric motor of the vehicle. In a hybrid vehicle, the electric motor is used primarily for low-speed cruising or to provide extra power for acceleration or hill climbing. When braking or coasting to a stop, the hybrid vehicle uses its electric motor as a generator to produce electricity, which is then stored in its battery pack. Thus, the electric motor in hybrid vehicles improves fuel economy compared to a vehicle equipped only with an internal combustion engine. Unlike all-electric vehicles, which have a limited travel range and create inconvenience for users by requiring frequent recharging at charging sites, hybrid vehicles do not need to be plugged into an external source of electricity to charge batteries.

However, hybrid vehicles present challenges to be addressed in order to be suitable for widespread implementation. For economic feasibility of the hybrid vehicle, which can be more expensive than a non-hybrid vehicle, cost should be minimized and advantages should be attained from other vehicle operational considerations. Emissions caused by the internal combustion engine should be reduced or eliminated if possible. The weight and size considerations involved with the use of both electric motor propulsion and an internal combustion engine with its fuel supply are important factors in vehicles such as compact cars and trucks.

Hybrid vehicles and all-electric vehicles each have their advantages and disadvantages. Each type of vehicle obtains benefits from the provision of a range extender. The need exists for a portable range extender that can be electrically connected to an all-electric vehicle to enable the vehicle to travel longer distances if necessary. For shorter travel distances that do not require range extender functionality, it would be desirable to avoid the weight of, and space occupied by, the unused range extender. The portability of a range extender would make it amenable to support vehicles of different types and be movable readily from one vehicle to another. Thus, it would be desirable that such portable range extender be operable independently of the controller of the vehicle. Improvements are also needed to reduce emissions and increase fuel efficiency.

#### Disclosure of Invention

The present invention fulfills the above described needs, at least in part, by provision of a portable range extender capable of supplying electrical energy to a vehicle. The range extender includes a dynamoelectric machine coupled to an internal combustion engine by a shaft. The dynamoelectric machine may be connected to a power source such as a vehicle battery, to operate as a motor to drive the shaft in rotation when a user initiates starting of the engine. The shaft, and thus the engine, accelerates in rotation while being driven by the dynamoelectric machine, the engine temperature increasing during this warm-up period. The rotational speed and engine temperature are sensed and, when optimal values for each of these parameters are obtained as determined by a dedicated range extender controller, fuel is supplied to the engine and ignition is activated. The engine then acts as a prime mover to further accelerate shaft rotation. As the engine

~~starts only upon optimal speed and~~ temperature conditions, fuel economy is maximized. With a warm start, fuel is burned most efficiently, thus minimizing emissions. As speed increases further, a level is reached at which the dynamoelectric machine can be activated as a generator to provide an electrical current output. At that time the engine has the prime mover capability to support the electrical power generation. The range extender controller outputs a signal in response to speed input for generator activation. When range extender operation is to be terminated, fuel supply to the engine is cut off and ignition is thereafter maintained for a preset period. The fuel remaining in the engine is efficiently burned, thereby avoiding engine backfire and accompanying emission of fumes.

Although the power generated by the range controller may be applied to charge the vehicle battery and/or drive the vehicle traction motor and other electrical loads, the range controller operations are under the control of an autonomous controller. The range extender and its controlling circuitry are self contained within an enclosure that is independent of a vehicle with which it may be used. An inverter/converter module, coupled to the controller, inverts the direct current supply to alternating current to the dynamoelectric machine when it is in motor operation and converts an alternating current output of the dynamoelectric machine to direct current when it is in generator operation. Also coupled to the controller are an ignition circuit, a fuel supply circuit, speed sensor and temperature sensor. The controller is also provided with user input terminals, thus permitting control of the range extender to be independent of the controller of the vehicle.

Additional advantages of the present invention will become readily apparent to those skilled in this art from the following detailed description, wherein only the preferred embodiment of the invention is shown and described, simply by way of illustration of the best mode contemplated of carrying out the invention. As will be realized, the invention is capable of other and different embodiments, and its several details are capable of modifications in various obvious respects, all without departing from the invention. Accordingly, the drawings and description are to be regarded as illustrative in nature, and not as restrictive.

#### Brief Description of the Drawings

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawing and in which like reference numerals refer to similar elements and in which:

Fig. 1 is a perspective view of range extender elements configured in a preferred embodiment of the present invention.

Fig. 2 is a view of the range extender elements of Fig. 1 shown with its enclosure.

Fig. 3 is a block diagram of controlled operation of the range extender of Fig. 1, shown in relation to an electric vehicle.

Fig. 4 is a block diagram of the fuel and ignition aspects of the range extender of Fig. 1.

Fig. 5 is a flow chart of range extender operation in accordance with the present invention.

#### Detailed Description of the Invention

Fig. 1 exemplifies a portable range extender 10 of the present invention. Prime mover 12, preferably an internal combustion engine, is coupled to dynamoelectric machine 14 by a common shaft. A controller and associated control circuitry are contained in a housing, the control system collectively indicated by reference numeral 16. As described further hereinafter, the control system is effective to control operations of both the engine 12 and the dynamoelectric machine 14. When operation of the range extender is initiated, the dynamoelectric machine 14 is controlled to operate as a motor for starting the engine 12. When prescribed engine conditions are detected, the control system 16 controls the dynamoelectric machine 14 to operate as a generator driven by the engine 12 to produce electrical power supplied to an external load. As a consequence of this control arrangement, there is no necessity for a separate starter motor for the engine, which is commonly provided in conventional motor-generator sets. The dynamoelectric machine 14 preferably may be a three phase AC electric machine, although other electrical machines may be employed. The three phase machine, which provides considerably more power than a conventional starter motor, can drive the engine at a higher speed in the starting mode and eliminates the need for a separate flywheel. Thus, the range extender 10 may be packaged in a compact integrated assembly covered by an enclosure 18, shown in phantom in Fig. 1, and further illustrated in Fig. 2. Within the enclosure, machine 14 and engine 12 are each contained in respective housings. The housing for engine 12 contains cool air inlet windows, one being indicated by reference numeral 20, in Fig. 1. The cool air inlet windows are in communication with corresponding windows 21 in the enclosure, as shown in Fig. 2. One or more hot air outlet windows 22 are provided in the enclosure. A divider 24 forms two chambers respectively for the engine and electrical machine. This arrangement provides efficient cooling as the cool air is directed first to the relatively cooler machine 14 and then to the engine 12. The enclosure is provided with a door 26 that easily may be opened to provide access for maintenance.

A compact structure is thus provided that enables a user to place the portable range extender into any battery-powered vehicle in order to extend its travel range by charging its battery or driving the vehicle instead of, or in combination with, the electric motor. For example, the range extender 10 may be placed in all-electric buses or vans to enable their use for longer trips. The range extender portability is also suitable for mounting in a trailer coupled to a vehicle. The range extender of the present invention may act as an auxiliary power unit not only for loads with substantial power consumption, such as trucks, recreational vehicles, etc., but may be used to supplement power requirements of any electrical load.

Fig. 3 is a block diagram of an exemplary embodiment of the present invention, in which the range extender 10 is detachably connectable to a battery-powered vehicle 100 having a traction electric motor 102 driven by a traction motor driver 104 and powered by a battery 106. The traction motor 102 may be, for example, a permanent magnet DC brushless motor, such as disclosed in patent 6,492,756, issued December 10, 2002 to Maslov et al., commonly assigned with the present invention. The high-voltage battery 106 can provide substantial electric power, for example, about 65 KW. The vehicle 100 is provided with an electric vehicle controller 108 for controlling typical operations of the electric vehicle. For example, in response to a torque request by the vehicle operator, the vehicle controller 108 may control the driver 104 to provide sufficient electric power from the battery 106 to the motor 102 to achieve the desired torque. The vehicle controller also may control the motor 102 to act as an electric generator to charge the battery 106 during a regeneration mode.

The range extender 10 is provided with an autonomous controller 30, such as a microcontroller, included within control system 16. The controller has a plurality of inputs, including user inputs 32 and inputs from battery sensor 34, engine temperature sensor 36 and speed sensor 38. The battery sensor provides an indication of the state of charge of the vehicle battery 106. Temperature sensor 36 provides indication of the engine temperature and speed sensor 38 provides a shaft speed feedback signal. The microcontroller can be programmable to control operations of the range extender in one or more modes. User inputs permit a user to select a particular operating mode or a manual operating mode.

Inverter/converter module 40 is detachably connectable to the vehicle 100 to provide a bidirectional transfer of power either from the battery 106 to the dynamoelectric machine 14 operating in the motoring mode during engine startup or from the dynamoelectric machine 14 operating in the generating mode to the battery 106. Under supervision of controller 30, module 40 operates to invert DC power from the battery 106 into 3-phase AC power for rotating the dynamoelectric machine 14 in the motoring mode, and converts 3-phase AC power generated by the dynamoelectric machine in the generating mode to DC power used for charging the battery 106 or driving the traction motor 102. Controller 30 is responsive to the range extender shaft speed as received from speed sensor 38 activate a switch circuit in the module 40 to activate generating operation when engine speed has obtained an appropriate level for driving the electrical machine 14. Controller 30 also provides output control signals to fuel supply circuit 42 and ignition circuit 44 during startup and turnoff phases of engine operation. As shown in Fig. 4, the fuel control circuit is responsive to controller 30 to regulate valve 48 and the flow of fuel from fuel supply 46 to engine 14. Valve 48 may be controlled to be switched between fully open or fully closed, or may be made variable between these extremes.

Fig. 5 is a flow chart of range extender operation. At step 200, a start command is issued, which may be initiated by a manual user operation, such as activation of a start switch. Alternatively, the start command may be issued pursuant an automatic operating mode of the controller. At step 202, controller 30 outputs control signals to module 40 to connect the battery 106 through a switch circuit in module 40 to machine 14 and to activate inverter operation. Dynamoelectric machine 14 thus receives alternating current power to operate as a motor to drive the shaft of the engine 12 and start the engine. Throughout operation, engine speed and temperature are sensed and input to the controller. At step 204, determination is made as to whether the shaft speed is at a sufficient level, S1, for engine operation. If not, machine motoring continues and step 204 is repeated. When the shaft speed has been determined to exceed S1, the sensed engine temperature is compared to a preset temperature threshold T1 at step 206. T1 represents the minimum engine temperature at which the engine can operate with satisfactory fuel efficiency. If the sensed temperature does not exceed T1, the engine continues to be driven by dynamoelectric machine 14 operating in a motoring mode and step 206 is repeated. When temperature threshold T1 is exceeded, the controller outputs control signals to fuel supply circuit 42 and ignition circuit 44 to initiate engine operation as a prime mover, at step 208. A control signal is also applied to module 40 to cease inverter operation, thus discontinuing operation of the machine 14 as a motor. Machine 14 thereafter will be operated as a generator to provide power for recharging battery 106 and/or to supply the traction motor 102. The minimum engine speed at which satisfactory generation can be achieved is represented by speed S2. Generally, S2 is greater than S1. At step 210, the sensed engine speed is compared with the threshold speed S2. S2 can be set in accordance with the expected electrical requirements of the particular battery and traction motor provided in the vehicle. Step 210 is repeated until the sensed speed is determined to have exceeded S2. At that time, the controller transmits a control signal to the module 40 at step 212. Module 40 is switched to provide direct current power, which is converted from the alternating current output of machine 14 operating as a generator, to the vehicle load.

Generator operation continues until a stop command is detected at step 214. The stop command may be sensed by the controller in response to a user input or in accordance with an automatic mode operation corresponding to a stored program. For example, such program may operate to initiate and terminate range extender operation in accordance with the state of charge of the battery. When the state of charge of the battery attains a level approaching a maximum, a stop command may be generated. In response to a stop command, the controller outputs a control signal to the fuel supply circuit 42 whereby valve 48 will be closed to terminate fuel supply to the engine. After a preset time delay D1 has occurred, as determined in step 281, the controller outputs a control signal to ignition circuit 44 to turn the engine ignition off at step 220. The time delay



between cutoff of fuel supply and ignition termination avoids engine backfire and the emissions associated with backfire.

In this disclosure there are shown and described only preferred embodiments of the invention and but a few examples of its versatility. It is to be understood that the invention is  
5 capable of use in various other combinations and environments and is capable of changes or modifications within the scope of the inventive concept as expressed herein. For example, it is within the contemplation of the invention that the range extender 10 may be utilized as an electric power source for providing electric power to loads with substantial power consumption, such as trucks, recreational vehicles, etc. As the extender is portable for use with different loads at different  
10 times, the autonomous extender controller provides flexibility in setting the various thresholds tailored to the particular loads with which the range extender can be utilized.

What is claimed is:

1. A method for controlling a portable range extender capable of supplying electrical energy to a vehicle, the range extender including a dynamoelectric machine coupled to an internal combustion engine by a shaft, the method comprising the steps of:
  - applying electrical energization from a power source to the dynamoelectric machine for operation thereof as a motor to drive the shaft in rotation in response to an initiation input;
  - sensing the rotational speed of the shaft;
  - sensing the temperature of the engine;
  - in response to a sensed rotational speed that meets a first predetermined speed threshold and a sensed engine temperature that meets a predetermined temperature threshold, supplying fuel to the engine and activating ignition of the engine for operation thereof as a prime mover; and
  - after a period of engine prime mover operation, activating the dynamoelectric machine for operation thereof as a generator to provide an electrical current output.
2. A method as recited in claim 1, wherein:
  - the power source is a direct current source and the step of applying electrical energization to the dynamoelectric machine comprises inverting an output voltage of the direct current source to alternating current.
3. A method as recited in claim 2, wherein the direct current source is a battery for operation of a vehicle traction motor.
4. A method as recited in claim 3, wherein the step of activating the dynamoelectric machine as a generator comprises producing an alternating current output of the dynamoelectric machine and converting the alternating current output to a direct current output;
  - and further comprising the step of applying the direct current output to charge the battery.
5. A method as recited in claim 4, further comprising the step of applying the direct current output to drive the traction motor.
6. A method as recited in claim 1, wherein said period of engine prime mover operation is a predetermined time interval.

7. A method as recited in claim 1, wherein dynamoelectric machine generator operation is activated when the sensed shaft rotational speed meets a second predetermined speed threshold higher than the first predetermined threshold.

5 8. A method as recited in claim 1, further comprising the steps of:

terminating the supply of fuel to the engine when the engine is to be stopped;  
maintaining ignition activation of the engine after the fuel supply has been terminated; and  
deactivating engine ignition when fuel has been eliminated from the engine, thereby to avoid engine backfire.

10

9. A method as recited in claim 8, wherein the deactivating step is delayed for a preset time period.

10. A method as recited in claim 8, wherein the range extender is self contained within an enclosure that is independent of a vehicle and the steps of applying electrical energization to the dynamoelectric machine, supplying fuel to the engine, activating ignition of the engine, activating  
15 the dynamoelectric machine, terminating the supply of fuel and deactivating engine ignition, are controlled by a controller contained within the enclosure.

11. A portable range extender capable of supplying electrical energy to a vehicle having a vehicle  
20 controller, the portable range extender comprising:

an internal combustion engine;  
a dynamoelectric machine structurally coupled to the internal combustion engine by a shaft and electrically coupled to a direct current source;  
an autonomous range extender controller having at least one user input; and  
25 a portable enclosure in which the internal combustion engine, dynamoelectric machine and controller are housed; wherein

in response to a user input to the controller, a sequence of range extender operations is initiated including a first phase in which electrical energization is applied from the direct current source to the dynamoelectric machine for operation thereof as a motor to drive the shaft in rotation,  
30 a second phase in which the engine is activated for operation as a prime mover; and a third phase in which the dynamoelectric machine is activated in generator operation for providing electrical current to the vehicle.

12. A portable range extender as recited in claim 11, wherein the internal combustion engine  
35 comprises an ignition circuit and a fuel supply circuit, each of these circuits coupled to a respective output of the controller.

13. A portable range extender as recited in claim 12, further comprising a speed sensor indicative of shaft speed and an engine temperature sensor, each of these sensors coupled to a respective speed input and temperature input of the controller.

5

14. A portable range extender as recited in claim 13, wherein the controller is configured to output signals to the ignition circuit and fuel supply circuit for prime mover activation in response to signals at the speed and temperature inputs attaining respective threshold values.

10 15. A portable range extender as recited in claim 12, the controller is responsive to a user termination input to apply an output signal to the fuel supply circuit to shut off the supply of fuel to the engine and, after a preset time delay, to output a signal to the ignition circuit to terminate engine ignition, thereby to avoid engine backfire.

15 16. A portable range extender as recited in claim 11, further comprising an inverter/converter circuit connected to electrical terminals of the dynamoelectric machine and to the controller; and wherein the inverter/converter circuit is responsive to the controller to convert the direct current energization applied in the first phase to the dynamoelectric machine to alternating current for motoring operation, and to invert alternating current output of the dynamoelectric machine in the  
20 third phase for generator operation.




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5

# INTERNATIONAL SEARCH REPORT

In International Application No  
PCT/US2005/002018

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B60K6/04 B60L11/12 F02N11/08

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B60K B60L F02N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 274 943 B1 (HASEGAWA YUSUKE ET AL) 14 August 2001 (2001-08-14)	1-6,8-10
Y	claim 8	7,11-16
Y	WO 01/79012 A (AIRTRAX CORPORATION; HARRIS, DONALD, B; AMICO, PETER) 25 October 2001 (2001-10-25) paragraph '0057!; claim 2	7,11-16
X	US 1 111 510 A (WARD) 22 September 1914 (1914-09-22) claims; figures	11,12
A	WO 00/74964 A (LAWSON, KEVIN, JON) 14 December 2000 (2000-12-14) page 7, last paragraph	1-16
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

29 June 2005

Date of mailing of the international search report

19/07/2005


Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bufacchi, B

## INTERNATIONAL SEARCH REPORT

In  tional Application No  
PCT/US2005/002018

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 249 806 A (MAGNET-MOTOR GMBH; MAGNET-MOTOR GESELLSCHAFT FUER MAGNETMOTORISCHE TEC) 23 December 1987 (1987-12-23) claims 5,6 -----	1-16
A	US 5 264 764 A (KUANG ET AL) 23 November 1993 (1993-11-23) cited in the application claims 9-11 -----	1-16
A	US 2002/096375 A1 (SCHMITZ ROBERT W ET AL) 25 July 2002 (2002-07-25) cited in the application claims 1,5 -----	1-16
A	US 6 333 620 B1 (SCHMITZ ROBERT W ET AL) 25 December 2001 (2001-12-25) cited in the application claims 3,5 -----	1-16
A	US 3 497 027 A (ALBERT F. WILD) 24 February 1970 (1970-02-24) * Fig. 6, electric starter motor 108 *claim 4 -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US2005/002018

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6274943	B1	14-08-2001	JP 3347080 B2 JP 2000186654 A	20-11-2002 04-07-2000
WO 0179012	A	25-10-2001	AU 5347301 A WO 0179012 A2 US 2001052433 A1	30-10-2001 25-10-2001 20-12-2001
US 1111510	A		NONE	
WO 0074964	A	14-12-2000	WO 0074964 A1	14-12-2000
EP 0249806	A	23-12-1987	DE 3620362 A1 AT 71888 T DE 3776206 D1 EP 0249806 A1 ES 2030401 T3	23-12-1987 15-02-1992 05-03-1992 23-12-1987 01-11-1992
US 5264764	A	23-11-1993	DE 4341817 A1	23-06-1994
US 2002096375	A1	25-07-2002	EP 1225073 A2 US 2004007404 A1 US 2004026142 A1	24-07-2002 15-01-2004 12-02-2004
US 6333620	B1	25-12-2001	EP 1193108 A2	03-04-2002
US 3497027	A	24-02-1970	NONE	